

**ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS**

Client:  
Project:  
Type:  
Quantity:

**CONSTRUCTION**

Sturdy thermoplastic, injection molded, 5VA flame retardant, high impact resistant housing.

**OPTICS**

Two "EXIT" Faceplates (with optional knockout arrows) and one blank faceplate included.

Color-matched diffuser eliminates hot spots and striations, providing optimal light output.

Exit sign meeting 100ft visibility compliant with UL requirement.

Emergency light capable of 0-90° horizontal x 180° vertical rotation.



LED Exit Sign with Emergency Lights RED Letters

**ELECTRICAL**

1.5W output per emergency light, total 3.1W consumption.

120-277V input.

3.6V 1000mAh Ni-Cad battery, 24hr for full charge at initial use or on depleted battery.

0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

**MOUNTING**

Suitable for ceiling mount, wall mount, mounting canopy included.

**STANDARD FINISH**

Black Finish

White Finish

**CERTIFICATION**

UL-94V-0 Flame Rating.

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.

All luminaires are built to UL924 standards and bear appropriate cETLus labels.

**WARRANTY**

5 year warranty, see Limited Warranty for additional information.

**SHIPPING DATA**

Product	Measurement	Weight
ES-L	17"L x 4"W x 8"H	4 lb



**ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS**

ORDER INFORMATION		EXAMPLE: ES-L R WH EM		
Fixture	Series	"Exit" Color	Finish	Input
	<b>ES-L</b>	<b>R</b>	<b>WH</b>	<b>EM</b>
<b>A SERIES</b>				
ES-L	LED Exit Sign with Dual Emergency Lights			
<b>B "EXIT" COLOR</b>				
Code	Color			
<b>G</b>	Green			
<b>R</b>	Red			
<b>C FINISH</b>				
<b>BK</b>	Black			
<b>WH</b>	White			
<b>D INPUT</b>				
<b>EM</b>	120 Minute Battery			
<b>E ACCESSORIES/OPTIONS</b>				
<b>BAA</b>	Assembled in America, compliant with BAA (COTS)			

**ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS**

**DIMENSIONS**

Series	L1	L2	H	W1	W2
ES-L	17.00" (431.80mm)	11.73" (297.94mm)	7.36" (186.95mm)	4.32" (109.73mm)	1.97" (49.96mm)

