

ES-L-RG SERIES EXIT SIGN with EMERGENCY LIGHTS

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Engineering grade injection-molded thermoplastic. 5VA flame retardant, impact resistant.

OPTICS

Double "EXIT" faceplates. (optional knockout arrows) included.
Red / Green letters switchable.



Switchable Red/Green color "EXIT" Letters

ELECTRICAL

1.5W output per emergency light, total 3.1W consumption.
Smart voltage input 120-277 VAC operation. LED display indicates AC/ON.
An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit. Built-in 3.6V700mAH rechargeable Ni-cd battery for minimum 120 minutes emergency operation
0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

MOUNTING

Easy to install. Universal mounting canopy for top or side installation.
Mounting canopy, installation instructions & hardware (inside unit).

STANDARD FINISH

White finish.

CERTIFICATION

Meets Buy America Act requirements (COTS).
Damp location.
All luminaires are built to UL1598 standards and bear appropriate cETLus labels.
All luminaires are built to UL924 standards and bear appropriate cULus labels.

SHIPPING DATA

Product	Measurement	Weight
ES-L-RG	19"L x 8"W x 3"H	5 lb

WARRANTY

5 year warranty, see Limited Warranty for additional information



ES-L-RG SERIES EXIT SIGN with EMERGENCY LIGHTS

ORDER INFORMATION				EXAMPLE: ES RG WH EM
Fixture	Series	“EXIT” Color	Finish	Input
	ES-L	RG	WH	EM
Options				
A	SERIES			
	ES-L	Exit Sign with Emergency Lights		
B	“EXIT” COLOR			
	Code	Color		
	RG	Red / Green Switchable		
C	FINISH			
	WH	White		
D	INPUT			
	EM	120 Minute Battery		
E	OPTIONS			
	AIA	Assembled in America, compliant with BAA (COTS)		

ES-L-RG SERIES EXIT SIGN with EMERGENCY LIGHTS

DIMENSIONS

Series	L1	L2	H	D
ES-L-RG	18.06" (459mm)	11.61" (295mm)	7.17" (182mm)	2.82" (72mm)

