



ES-EDGE SERIES EDGELIT EXIT SIGN

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Extruded aluminum mounting canopy.

OPTICS

Constructed of clear acrylic. Stencil letters are 6" high with 3/4" stroke, with minimum of 100 ft. viewing distance rating as required by UL 924 standard. Double face panels are supplied with a mirror insert. High output red or green LEDs provide superior brightness. Energy consumption of less than 3W for AC only and less than 5W for battery back-up units. LEDs are a maintenance-free solution, providing up to 100,000 hours of use without failure.

ELECTRICAL

Dual-voltage input 120 or 277VAC at 60Hz.
Built-in 4.8V 600mAH rechargeable Ni-MH battery for minimum 120 minutes emergency operation. Batteries offer high discharge rates and continue to perform in a vast temperature range from 32°F to 104°F (0°C to 40°C).

MOUNTING

Suitable for wall, sloped, high or standard ceiling mounting. Includes field installable directional arrow indicators.

STANDARD FINISH

Brushed Aluminum.

CUSTOM FINISH

Black, White Finish.

CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cULus labels.
All luminaires are built to UL924 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information



Green "EXIT" Letters



Red "EXIT" Letters

SHIPPING DATA

Product	Measurement	Weight
ES-EDGE	14"L x 10"W x 3"H	4 lb



ES-EDGE SERIES EDGELIT EXIT SIGN

ORDER INFORMATION		EXAMPLE: ES-EDGE R BA EM		
Fixture	Series	"EXIT" Color	Finish	Input
ES-EDGE				
A	SERIES			
	ES-EDGE	Edgelit LED Exit Sign		
B	"EXIT" COLOR			
	Code	Color		
	G	Green		
	R	Red		
C	FINISH			
	Standard			
	BA	Brushed Aluminum		
	Optional Color			
	BK	Black	WH	White
D	INPUT			
	EM	120 Minute Battery		
F	ACCESSORIES/OPTIONS			
	BAA	Assembled in America, compliant with BAA (COTS)		

ES-EDGE SERIES EDGELIT EXIT SIGN

DIMENSIONS

Series	L1	L2	D1	D2	H1	H2
ES-EDGE	12.31" (313mm)	11.22" (285mm)	4.45" (113mm)	0.31" (8mm)	6.75" (171mm)	9.89" (251mm)

