



## ESW SERIES WET LOCATION EXIT SIGN

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Engineering grade injection-molded thermoplastic. 5VA flame retardant, impact resistant water tight housing.

### OPTICS

Red "EXIT". (optional knockout arrows)

### ELECTRICAL

Smart voltage input 120-277 VAC operation. LED display indicates AC/ON. An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit. Built-in 4.8V700mAH rechargeable Ni-cd battery for minimum 120 minutes emergency operation 0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

### MOUNTING

Wall Mount through housing.

### STANDARD FINISH

White finish.

### CERTIFICATION

Wet Location.

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.  
All luminaires are built to UL924 standards and bear appropriate cULus labels.

### WARRANTY

5 year warranty, see Limited Warranty for additional information



### SHIPPING DATA

Product	Measurement	Weight
ESW	14"L x 9"W x 3"H	5 lb



**ESW SERIES WET LOCATION EXIT SIGN**

ORDER INFORMATION					EXAMPLE: ESW R WH EM
Fixture	Series	“EXIT” Color	Finish	Mounting	Input
	<b>ESW</b>	<b>R</b>	<b>WH</b>	<b>blank</b>	<b>EM</b>
<b>A</b>	<b>SERIES</b>				
	ES	LED Exit Sign			
<b>B</b>	<b>“EXIT” COLOR</b>				
	Code	Color			
	R	Red “EXIT”			
<b>C</b>	<b>FINISH</b>				
	WH	White			
<b>D</b>	<b>MOUNTING</b>				
	blank	Wall Mount			
<b>E</b>	<b>INPUT</b>				
	EM	120 Minute Battery			
<b>F</b>	<b>ACCESSORIES/OPTIONS</b>				
	BAA	Assembled in America, compliant with BAA (COTS)			

**ESW SERIES WET LOCATION EXIT SIGN**

**DIMENSIONS**

Series	L	H	D
ESW-R	13.39" (340mm)	8.58" (218mm)	2.10" (53mm)

