

## EL-RH SERIES REMOTE EMERGENCY LIGHT

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Aluminum J-Box Cover. Emergency light made with ABS thermoplastic material, spec-grade product obtain UL-94-5VA rating.

Emergency heads are individually adjustable 360° rotation and up to 90° tilt.



### OPTICS

Polycarbonate prismatic lens.

### ELECTRICAL

-30°C up to 50°C (-22°F up to 122°F) maximum operating temperature.

Lamps use long-lasting, efficient ultra bright white LEDs.

Adjustable Single Head 1.2W / Dual Head 2 x 1.2W LED heads equipped with 12 series-parallel white LEDs each.

3.6V ~ 9.6V Input, maintenance-free.

### MOUNTING

Includes a universal mounting base plate with mounting hardware. The distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run. Suitable for wall or ceiling mount.

Suggested mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 18ft for a 3ft path of egress.

### STANDARD FINISH

White finish.

### CERTIFICATION

All luminaires are built to UL1598 & UL924 standards and bear appropriate cULus labels. Emergency light carries UL-94-5VA Rating.

### SHIPPING DATA

Product	Measurement	Weight
EL-RH-S	7" L x 4" W x 3" H	2 lb
EL-RH-D	7" L x 4" W x 5" H	3 lb

### WARRANTY

5 year warranty, see Limited Warranty for additional information



**EL-RH SERIES REMOTE EMERGENCY LIGHT****ORDER INFORMATION****EXAMPLE : EL RH D**

Fixture      SERIES      POWER

**EL-RH****A SERIES**

EL-RH      Remote Emergency Light

**B POWER & LM**

	Power	LM
S	Single 1.2W Head	175lm
D	Double 1.2W Heads	350lm

## EL-RH SERIES REMOTE EMERGENCY LIGHT

### DIMENSIONS

Power	W1	W2	H1	H2
EL-RH-S	4.53" (115mm)	3.72" (95mm)	6.33" (161mm)	3.72" (95mm)
EL-RH-D	4.53" (115mm)	10.27" (261mm)	6.06" (154mm)	

