

EL-B SERIES STEEL ENCLOSURE EMERGENCY LIGHT

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Rugged 20-Gauge steel housing. Emergency light made with ABS thermoplastic material, spec-grade product obtain UL-94-5VA rating.
Emergency heads are individually adjustable 360° rotation and up to 90° tilt.

OPTICS

Polycarbonate prismatic lens.

ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature.
Lamps use long-lasting, efficient ultra bright white LEDs.
Adjustable 2 x 1.2W LED heads equipped with 12 series-parallel white LEDs each.
120-277V Input, maintenance-free 4.8V 1000mAh Ni-MH battery that provides a minimum emergency duration of 120 minutes.

MOUNTING

Surface mount through luminaire body, allow mounting on 4" Round or Square J-box.
Suggested mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 18ft for a 3ft path of egress.

EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 120 minutes.
Recharge a discharged battery in 24 hours.

STANDARD FINISH

White finish metal housing with light gray finish heads.

CERTIFICATION

All luminaires are built to UL1598 & UL924 standards and bear appropriate cULus labels.
Emergency light carries UL-94-5VA Rating.

WARRANTY

5 year warranty, see Limited Warranty for additional information



SHIPPING DATA

Product	Measurement	Weight
ELB	13"L x 5"W x 6"H	10 lb



EL-B SERIES STEEL ENCLOSURE EMERGENCY LIGHT

ORDER INFORMATION				EXAMPLE : EL B WH EM
Fixture	SERIES	POWER	FINISH	INPUT
	EL	B	WH	EM
A	SERIES			
	EL	Emergency Light		
B	POWER & LM			
		Power	LM	
B		2 x 1.2W	175lm	
C	FINISH			
	WH	White		
D	INPUT			
	EM	120 Minute Battery		
E	ACCESSORIES/OPTIONS			
	BAA	Assembled in America, compliant with BAA (COTS)		

EL-B SERIES STEEL ENCLOSURE EMERGENCY LIGHT

DIMENSIONS

Power	L1	L2	L3	H1	H2	W1	W2
EL-B	12.38" (290mm)	10.22" (260mm)	6.50" (165mm)	4.94" (125mm)	10.29" (262mm)	2.61" (66mm)	3.06" (78mm)

