

## ES-EDGE SERIES EDGELIT EXIT SIGN

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Extruded aluminum mounting canopy.

### OPTICS

Constructed of clear acrylic. Stencil letters are 6" high with 3/4" stroke, with minimum of 100 ft. viewing distance rating as required by UL 924 standard. Double face panels are supplied with a mirror insert. High output red or green LEDs provide superior brightness. Energy consumption of less than 3W for AC only and less than 5W for battery back-up units. LEDs are a maintenance-free solution, providing up to 100,000 hours of use without failure.

### ELECTRICAL

Dual-voltage input 120 or 277VAC at 60Hz.  
Built-in 4.8V 600mAH rechargeable Ni-MH battery for minimum 90 minutes emergency operation. Batteries offer high discharge rates and continue to perform in a vast temperature range from 32°F to 104°F (0°C to 40°C).

### MOUNTING

Suitable for wall, sloped, high or standard ceiling mounting. Includes field installable directional arrow indicators.

### STANDARD FINISH

Brushed Aluminum.

### CUSTOM FINISH

Black, White Finish.

### CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cULus labels.  
All luminaires are built to UL924 standards and bear appropriate cULus labels.

### WARRANTY

5 year warranty, see Limited Warranty for additional information



Green "EXIT" Letters



Red "EXIT" Letters

### SHIPPING DATA

Product	Measurement	Weight
ES-EDGE	14"L x 10"W x 3"H	4 lb



## ES-EDGE SERIES EDGELIT EXIT SIGN

ORDER INFORMATION				EXAMPLE: ES-EDGE R BA EM	
Fixture	Series	“EXIT” Color	Finish	Input	
ES-EDGE					
A	SERIES				
ES-EDGE	Edgelit LED Exit Sign				
B	“EXIT” COLOR				
Code	Color				
G	Green				
R	Red				
C	FINISH				
Standard					
BA	Brushed Aluminum				
Optional Color					
	BK	Black	WH	White	
D	INPUT				
EM	90 Minute Battery				

## ES-EDGE SERIES EDGELIT EXIT SIGN

### DIMENSIONS

Series	L1	L2	D1	D2	H1	H2
ES-EDGE	12.31" (313mm)	11.22" (285mm)	4.45" (113mm)	0.31" (8mm)	6.75" (171mm)	9.89" (251mm)

