

ELW SERIES WET LOCATION EMERGENCY LIGHT

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Injection-molded thermoplastic material. Spec-grade product obtain UL-94-5VA rated. Fully adjustable emergency lights offers 360° rotation and 90° tilt.

OPTICS

Polycarbonate prismatic lens.

ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature.

Lamps use long-lasting, efficient ultra bright white LEDs.

Adjustable 2 x 1.2W LED heads equipped with 12 series-parallel white LEDs each. 60Hz, 120-277V Input, maintenance-free 3.6V 700mAh Nickel Cadmium battery that provides a minimum emergency duration of 120 minutes.

MOUNTING

Surface mount through luminaire body, allow mounting on 4" Round or Square J-box. Suggested mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 28ft for a 3ft path of egress.

EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 120 minutes. Recharge a discharged battery in 24 hours.

STANDARD FINISH

White finish with clear water tight cover.

CERTIFICATION

All luminaires are built to UL1598 & UL924 standards and bear appropriate cULus labels. UL94-5VA Rating.

WARRANTY

5 year warranty, see Limited Warranty for additional information



SHIPPING DATA

Product	Measurement	Weight
ELW-A	12"L x 5"W x 5"H	3 lb



ELW SERIES WET LOCATION EMERGENCY LIGHT

ORDER INFORMATION				EXAMPLE : ELW A WH EM
Fixture	SERIES	POWER	FINISH	INPUT
	ELW	A	WH	EM
A	SERIES			
	ELW	Wet Location Emergency Light		
B	POWER & LM			
	Power	LM		
A	2 x 1.2W	175lm		
C	FINISH			
	WH	White		
D	INPUT			
	EM	120 Minute Battery		
E	ACCESSORIES/OPTIONS			
	BAA	Assembled in America, compliant with BAA (COTS)		

ELW SERIES WET LOCATION EMERGENCY LIGHT

DIMENSIONS

Power	L	W	H
ELW-A	11.61" (295mm)	4.71" (112mm)	4.13" (105mm)

