

## ELW SERIES WET LOCATION EMERGENCY LIGHT

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Injection-molded thermoplastic material. Spec-grade product obtain UL-94-5VA rated.  
Fully adjustable emergency lights offers 360° rotation and 90° tilt.

### OPTICS

Polycarbonate prismatic lens.

### ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature.

Lamps use long-lasting, efficient ultra bright white LEDs.

Adjustable 2 x 1.2W LED heads equipped with 12 series-parallel white LEDs each.

120-277V Input, maintenance-free 3.6V 700mAh Nickel Cadmium battery that provides a minimum emergency duration of 90 minutes.

### MOUNTING

Surface mount through luminaire body, allow mounting on 4" Round or Square J-box.  
Suggested mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 28ft for a 3ft path of egress.

### EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 90 minutes.  
Recharge a discharged battery in 24 hours.

### STANDARD FINISH

White finish with clear water tight cover.

### CERTIFICATION

All luminaires are built to UL1598 & UL924 standards and bear appropriate cULus labels.  
UL94-5VA Rating.

### WARRANTY

5 year warranty, see Limited Warranty for additional information



### SHIPPING DATA

Product	Measurement	Weight
ELW-A	12"L x 5"W x 5"H	3 lb



## ELW SERIES WET LOCATION EMERGENCY LIGHT

ORDER INFORMATION				EXAMPLE : ELW A WH EM
Fixture	SERIES	POWER	FINISH	INPUT
	ELW	A	WH	EM
<b>A</b>	SERIES			
ELW	Wet Location Emergency Light			
<b>B</b>	POWER & LM			
	Power	LM		
A	2 x 1.2W	175lm		
<b>C</b>	FINISH			
WH	White			
<b>D</b>	INPUT			
EM	90 Minute Battery			

**ELW SERIES WET LOCATION EMERGENCY LIGHT**

**DIMENSIONS**

Power	L	W	H
ELW-A	11.61" (295mm)	4.71" (112mm)	4.13" (105mm)

