

ELW SERIES WET LOCATION EMERGENCY LIGHT

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Injection-molded thermoplastic material. Spec-grade product obtain UL-94-5VA rated. Fully adjustable emergency lights offers 360° rotation and 90° tilt.



OPTICS

Polycarbonate prismatic lens.

ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Lamps use long-lasting, efficient ultra bright white LEDs. Adjustable 2 x 1.2W LED heads equipped with 12 series-parallel white LEDs each. 120-277V Input, maintenance-free 3.6V 700mAh Nickel Cadmium battery that provides a minimum emergency duration of 120 minutes.

MOUNTING

Surface mount through luminaire body, allow mounting on 4" Round or Square J-box. Suggested mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 28ft for a 3ft path of egress.

EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 120 minutes. Recharge a discharged battery in 24 hours.

SHIPPING DATA

Product	Measurement	Weight
ELW-A	12" L x 5" W x 5" H	3 lb

CERTIFICATION

All luminaires are built to UL1598 & UL924 standards and bear appropriate cULus labels. UL94-5VA Rating.

WARRANTY

5 year warranty, see Limited Warranty for additional information



ELW SERIES WET LOCATION EMERGENCY LIGHT

ORDER INFORMATION					EXAMPLE : ELW A WH EM
Fixture	SERIES	POWER	FINISH	INPUT	
	ELW	A	WH	EM	
A	SERIES				
ELW	Wet Location Emergency Light				
B	POWER & LM				
A	Power 2 x 1.2W	LM 175lm			
C	FINISH				
WH	White				
D	INPUT				
EM	120 Minute Battery				
E	ACCESSORIES/OPTIONS				
AIA	Assembled in America, compliant with BAA (COTS)				

ELW SERIES WET LOCATION EMERGENCY LIGHT

DIMENSIONS

Power	L	W	H
ELW-A	11.61" (295mm)	4.71" (112mm)	4.13" (105mm)

