

ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Sturdy thermoplastic, injection molded, 5VA flame retardant, high impact resistant housing.

OPTICS

Two "EXIT" Faceplates (with optional knockout arrows) and one blank faceplate included.

Color-matched diffuser eliminates hot spots and striations, providing optimal light output.

Exit sign meeting 100ft visibility compliant with UL requirement.

Emergency light capable of 0-90° horizontal x 180° vertical rotation.



LED Exit Sign with Emergency Lights RED Letters

ELECTRICAL

1.5W output per emergency light, total 3.1W consumption.

120-277V input.

3.6V 1000mAh Ni-Cad battery, 24hr for full charge at initial use or on depleted battery.

0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

MOUNTING

Suitable for ceiling mount, wall mount, mounting canopy included.

STANDARD FINISH

Black Finish

White Finish

SHIPPING DATA

Product	Measurement	Weight
ES-L	17"L x 4"W x 8"H	4 lb

CERTIFICATION

UL-94V-0 Flame Rating.

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.

All luminaires are built to UL924 standards and bear appropriate cETLus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information.



ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS

ORDER INFORMATION				EXAMPLE: ES-L R WH EM
Fixture	Series	“Exit” Color	Finish	Input
	ES-L	R	WH	EM
A	SERIES			
	ES-L	LED Exit Sign with Dual Emergency Lights		
B	“EXIT” COLOR			
	Code	Color		
	G	Green		
	R	Red		
C	FINISH			
	BK	Black		
	WH	White		
D	INPUT			
	EM	120 Minute Battery		
E	ACCESSORIES/OPTIONS			
	AIA	Assembled in America, compliant with BAA (COTS)		

ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS

DIMENSIONS

Series	L1	L2	H	W1	W2
ES-L	17.00" (431.80mm)	11.73" (297.94mm)	7.36" (186.95mm)	4.32" (109.73mm)	1.97" (49.96mm)

