

ES-EDGE SERIES EDGELIT EXIT SIGN

Client: Project: Type: Quantity:

CONSTRUCTION

Extruded aluminum mounting canopy.

OPTICS

Constructed of clear acrylic. Stencil letters are 6" high with 3/4" stroke, with minimum of 100 ft. viewing distance rating as required by UL 924 standard. Double face panels are supplied with a mirror insert. High output red or green LEDs provide superior brightness. Energy consumption of less than 3W for AC only and less than 5W for battery back-up units. LEDs are a maintenance-free solution, providing up to 100,000 hours of use without failure.

ELECTRICAL

Dual-voltage input 120 or 277VAC at 60Hz.

Built-in 4.8V 600mAH rechargeable Ni-MH battery for minimum 120 minutes emergency operation. Batteries offer high discharge rates and continue to perform in a vast temperature range from 32°F to 104°F (0°C to 40°C).

MOUNTING

Suitable for wall, sloped, high or standard ceiling mounting. Includes field installable directional arrow indicators.

STANDARD FINISH

Brushed Aluminum.

CUSTOM FINISH

Black. White Finish.

CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cULus labels. All luminaires are built to UL924 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information



Green "EXIT" Letters



Red "EXIT" Letters

SHIPPING DATA

Product Measurement Weight ES-EDGE 14"L x 10"W x 3"H 4 lb





ES-EDGE SERIES EDGELIT EXIT SIGN

ORDER INFORMATION EXAMPLE: ES-EDGE R BA EM

Fixture Series "EXIT" Color Finish Input

ES-EDGE

A SERIES

ES-EDGE Edgelit LED Exit Sign

B "EXIT" COLOR

Code Color G Green R Red

C FINISH

Standard

BA Brushed Aluminum

Optional Color

BK Black WH White

D INPUT

EM 120 Minute Battery

ACCESSORIES/OPTIONS

AIA Assembled in America, compliant with BAA (COTS)



ES-EDGE SERIES EDGELIT EXIT SIGN

DIMENSIONS

Series	L1	L2	D1	D2	H1	H2
ES-EDGE	12.31" (313mm)	11.22" (285mm)	4.45" (113mm)	0.31" (8mm)	6.75" (171mm)	9.89" (251mm)





