

## EL-B SERIES STEEL ENCLOSURE EMERGENCY LIGHT

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Rugged 20-Gauge steel housing. Emergency light made with ABS thermoplastic material, spec-grade product obtain UL-94-5VA rating.

Emergency heads are individually adjustable 360° rotation and up to 90° tilt.

### OPTICS

Polycarbonate prismatic lens.

### ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature.

Lamps use long-lasting, efficient ultra bright white LEDs.

Adjustable 2 x 1.2W LED heads equipped with 12 series-parallel white LEDs each.

120-277V Input, maintenance-free 4.8V 1000mAh Ni-MH battery that provides a minimum emergency duration of 90 minutes.

### MOUNTING

Surface mount through luminaire body, allow mounting on 4" Round or Square J-box.

Suggested mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 18ft for a 3ft path of egress.

### EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 90 minutes.

Recharge a discharged battery in 24 hours.

### STANDARD FINISH

White finish metal housing with light gray finish heads.

### CERTIFICATION

All luminaires are built to UL1598 & UL924 standards and bear appropriate cULus labels.

Emergency light carries UL-94-5VA Rating.

### WARRANTY

5 year warranty, see Limited Warranty for additional information



### SHIPPING DATA

Product	Measurement	Weight
ELB	13"L x 5"W x 6"H	10 lb



## EL-B SERIES STEEL ENCLOSURE EMERGENCY LIGHT

ORDER INFORMATION				EXAMPLE : EL B WH EM	
Fixture		SERIES	POWER	FINISH	INPUT
		EL	B	WH	EM
A	SERIES				
	EL	Emergency Light			
B	POWER & LM				
		Power	LM		
	B	2 x 1.2W	175lm		
C	FINISH				
	WH	White			
D	INPUT				
	EM	90 Minute Battery			

## EL-B SERIES STEEL ENCLOSURE EMERGENCY LIGHT

### DIMENSIONS

Power	L1	L2	L3	H1	H2	W1	W2
EL-B	12.38" (290mm)	10.22" (260mm)	6.50" (165mm)	4.94" (125mm)	10.29" (262mm)	2.61" (66mm)	3.06" (78mm)

