

ESW SERIES WET LOCATION EXIT SIGN

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Engineering grade injection-molded thermoplastic. 5VA flame retardant, impact resistant water tight housing.

OPTICS

Red "EXIT". (optional knockout arrows)

ELECTRICAL

Smart voltage input 120-277 VAC operation. LED display indicates AC/ON.
An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit. Built-in 4.8V700mAH rechargeable Ni-cd battery for minimum 90 minutes emergency operation
0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

MOUNTING

Wall Mount through housing.

STANDARD FINISH

White finish.

CERTIFICATION

Wet Location.

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.
All luminaires are built to UL924 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information



SHIPPING DATA

Product	Measurement	Weight
ESW	14"L x 9"W x 3"H	5 lb



ESW SERIES WET LOCATION EXIT SIGN

ORDER INFORMATION					EXAMPLE: ESW R WH EM
Fixture	Series	“EXIT” Color	Finish	Mounting	Input
	ESW	R	WH	blank	EM
A	SERIES				
	ES	LED Exit Sign			
B	“EXIT” COLOR				
	Code	Color			
	R	Red “EXIT”			
C	FINISH				
	WH	White			
D	MOUNTING				
	blank	Wall Mount			
E	INPUT				
	EM	90 Minute Battery			

ESW SERIES WET LOCATION EXIT SIGN

DIMENSIONS

Series	L	H	D
ESW-R	13.39" (340mm)	8.58" (218mm)	2.10" (53mm)

