

ES-RG SERIES LED EXIT SIGN

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Engineering grade injection-molded thermoplastic. 5VA flame retardant, high-impact resistant.

OPTICS

Double "EXIT" faceplates. (optional knockout arrows) included.
Red / Green letters switchable.

ELECTRICAL

Smart voltage input 120-277 VAC, 60Hz. LED display indicates AC/ON. An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit.
0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

MOUNTING

Easy to install. Universal mounting canopy for top or side installation.
Mounting canopy, installation instructions & hardware (inside unit).

STANDARD FINISH

White / Black finish.

CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.
All luminaires are built to UL924 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information



Red / Green Letters Switchable

SHIPPING DATA

Product	Measurement	Weight
ES-RG	13"L x 8"W x 2"H	3 lb



ES-RG SERIES LED EXIT SIGN

ORDER INFORMATION				EXAMPLE: ES RG WH EM
Fixture	Series	“EXIT” Color	Finish	Input
	ES	RG		EM
A	SERIES			
	ES	LED Exit Sign		
B	“EXIT” COLOR			
	Code	Color		
	RG	Red / Green Switchable		
C	FINISH			
	BK	Black		
	WH	White		
D	INPUT			
	EM	120 Minute Battery		
E	ACCESSORIES/OPTIONS			
	BAA	Assembled in America, compliant with BAA (COTS)		

ES-RG SERIES LED EXIT SIGN

DIMENSIONS

Series	L	H	D
ES-RG	12.20" (310mm)	7.44" (189mm)	1.69" (43mm)

