

SMD-OP SERIES SURFACE MOUNT OPAL

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Offered in 11" and 14" sizes, the fixture features a high lumen transmission cover and is designed for surface mounting. Engineered for secure installation to standard junction boxes with enhanced durability and heat dissipation.

OPTICS

Durable PMMA lens, gasketed and sealed to prevent splash of water or dust from entry.

ELECTRICAL

80+ CRI.

120V Input, Triac Dimming.

5 CCT selectable light engine from 2700~5000K.

MOUNTING

Surface Mount.

STANDARD FINISH

White Finish.

CERTIFICATION

Suitable for damp location.

Meets Buy America Act requirements.

DLC Listed.

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.

FCC Certified.

Energy Star Certified.

WARRANTY

5 year warranty, see Limited Warranty for additional information.



SMD-OP SERIES SURFACE MOUNT OPAL

ORDER INFORMATION				EXAMPLE : SMD OP 11 SC WH S	
Fixture	Series	Model	CCT	Finish	Input
	SMD-OP		SC	WH	S
Accessories Options					
A	SERIES				
	SMD-OP	Surface Mount Opal			
B	MODEL				
	CODE	POWER	LM	BEAM ANGLE	
	11	20W	1400lm (avg.)	120°	
	14	26W	1820lm (avg.)	120°	
C	CCT				
	SC	Field Selectable 2700/3000/3500/4000/5000K			
D	FINISH				
	WH	White Finish			
E	INPUT				
	S	120V Input, Triac Dimming			
F	ACCESSORIES/OPTIONS				
	BAA	Assembled in America, compliant with BAA (COTS)			

SMD-OP SERIES SURFACE MOUNT OPAL

DIMENSIONS

MODEL	W	H
SMD-OP-11	Ø 11" (279mm)	3.75" (95mm)
SMD-OP-14	Ø 14" (356mm)	4.5" (114mm)



APPLICATION

Surface Mount
 (Standard)

