

SMD-DR SERIES SURFACE MOUNT DOUBLE RING

Client: _____
Project: _____
Type: _____
Quantity: _____

CONSTRUCTION

Offered in 10", 12", 14", and 16" sizes, the fixture features cold rolled steel plates and rings. Designed for surface mounting. Engineered for secure installation to standard junction boxes with enhanced durability and heat dissipation.

OPTICS

Durable PMMA material lens with high transmittance, and UV protection.

ELECTRICAL

80+ CRI.

120V Input, Triac Dimming.

5 CCT selectable light engine from 2700~5000K.

MOUNTING

Surface Mount.

STANDARD FINISH

Satin Nickel Finish.

CERTIFICATION

Suitable for damp location.

Meets Buy America Act requirements.

DLC Listed.

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.

FCC Certified.

Energy Star Certified.

WARRANTY

5 year warranty, see Limited Warranty for additional information.



SMD-DR SERIES SURFACE MOUNT DOUBLE RING

ORDER INFORMATION				EXAMPLE : SMD DR 11 SC SN S	
Fixture	Series	Model	CCT	Finish	Input
	SMD-DR		SC	SN	S
Accessories Options					
A	SERIES				
	SMD-DR	Surface Mount Double Ring			
B	MODEL				
	CODE	POWER	LM	BEAM ANGLE	
	10	16W	960lm (avg.)	120°	
	12	20W	1400lm (avg.)	120°	
	14	26W	1820lm (avg.)	120°	
	16	36W	2520lm (avg.)	120°	
C	CCT				
	SC	Field Selectable 2700/3000/3500/4000/5000K			
D	FINISH				
	SN	Satin Nickel Finish			
E	INPUT				
	S	120V Input, Triac Dimming			
F	ACCESSORIES/OPTIONS				
	BAA	Assembled in America, compliant with BAA (COTS)			

SMD-DR SERIES SURFACE MOUNT DOUBLE RING

DIMENSIONS

MODEL	W	H
SMD-DR-10	ø 10" (254mm)	2.5" (64mm)
SMD-DR-12	ø 12" (305mm)	2.5" (64mm)
SMD-DR-14	ø 14" (356mm)	2.6" (66mm)
SMD-DR-16	ø 16" (406mm)	2.8" (71mm)



APPLICATION

Surface Mount
 (Standard)

