

WSA SERIES WALL MOUNT CYLINDER SELECTABLE

Client: _____
 Project: _____
 Type: _____
 Quantity: _____

CONSTRUCTION

Housing, hood and mounting stem are precision-machined from corrosion resistant aluminum, sealed with a high temperature silicone O-ring gasket to prevent water intrusion.

OPTICS

Borosilicate glass lens is removable and accepts internal accessories such as filters to achieve multiple lighting effects. Weep holes prevent water and mineral stains from collecting on the lens, even in the straight up position.

Standard with Field CCT Selectable LED light engine for 3000K, 4000K, and 5000K (80 CRI).



Single

ELECTRICAL

80+ CRI Samsung LED.

-40°C up to 50°C (-40°F up to 122°F) maximum operating temperature.

100,000hr LED at L70 @ 25°C

Field Selectable Output Package (see order detail).

Driver operates at 120-277V input, 50/60Hz, <20% THD, 0.9 power factor.

Built-in photocell.

MOUNTING

Wall mount over electrical box.

STANDARD FINISH

Corrosion resistant Dark Bronze, Black and White powder coating finish.

CUSTOM FINISH

Corrosion resistant Graphite Metallic, Gray, Silver, or custom RAL#

SHIPPING DATA

Product	Measurement	Weight
WSA-S	7"L x 7"W x 7"H	5 lb

CERTIFICATION

IP65 Wet location listed.

Meets Buy America Act requirements.

All luminaires are built to UL1598 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information.




WSA SERIES WALL MOUNT CYLINDER SELECTABLE

ORDER INFORMATION				EXAMPLE: WSA S SC BK U P	
Fixture	Series	Power & LM	CCT	Finish	Input
	WSA		SC		U-P
Accessories					
Options					
A	SERIES				
WSA	Wall Cylinder - Dual Selectable				
B	POWER & LM				
Code	Power	LM			
S	Single - Field Selectable 6W / 8W / 10W	600lm / 800lm / 1,000lm			
C	CCT				
SC	Field Selectable CCT 3000K / 4000K / 5000K				
D	FINISH				
Standard					
DB	Dark Bronze	BK	Black	WH	White
Custom Color					
CC	GM	Graphite Metallic	GR	SV	Silver
	RAL#				
E	INPUT				
U-P	120-277V with Built-in Photocell				
	*see page 4 for spec				
F	ACCESSORIES/OPTIONS				
BAA	Assembled in America, compliant with BAA (COTS)				
SURGE-LSP4-U	10kV inline Surge Protection for Universal input / U: 120-277V				

WSA SERIES WALL MOUNT CYLINDER SELECTABLE

DIMENSIONS				
Model	H1	H2	W1	W2
WSA-S	6.50" (165mm)	4.71" (120mm)	ø4.30" (108mm)	7.00" (179mm)



WSA SERIES WALL MOUNT CYLINDER SELECTABLE

SENSOR SPEC

Model	Type	Mounting	Coverage	Input	Function	Programmable
SENSOR-PH-PB-U	-	-	-	Universal	Dusk-to-Dawn Control	-



SENSOR-PH-PB-U