

## ES-L-RG-G2 SERIES EXIT SIGN with EMERGENCY LIGHTS

Client:

Project:

Type:

Quantity:

### CONSTRUCTION

Engineering grade injection-molded thermoplastic. 5VA flame retardant, impact resistant.

### OPTICS

Double "EXIT" faceplates. (optional knockout arrows) included.  
Red / Green letters switchable.



### ELECTRICAL

1.5W output per emergency light, total 3.1W consumption.  
Smart voltage input 120-277 VAC operation. LED display indicates AC/ON.  
An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit. Built-in 3.6V700mAH rechargeable Ni-cd battery for minimum 120 minutes emergency operation  
0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

Switchable Red/Green color "EXIT" Letters

### MOUNTING

Easy to install. Universal mounting canopy for top or side installation.  
Mounting canopy, installation instructions & hardware (inside unit).

### STANDARD FINISH

White finish.

### CERTIFICATION

Meets Buy America Act requirements (COTS).  
Damp location.  
All luminaires are built to UL1598 standards and bear appropriate cETLus labels.  
All luminaires are built to UL924 standards and bear appropriate cULus labels.

### SHIPPING DATA

| Product    | Measurement         | Weight |
|------------|---------------------|--------|
| ES-L-RG-G2 | 19" L x 8" W x 3" H | 5 lb   |

### WARRANTY

5 year warranty, see Limited Warranty for additional information



## ES-L-RG-G2 SERIES EXIT SIGN with EMERGENCY LIGHTS

| ORDER INFORMATION                    |   |              |           |           | EXAMPLE: ES RG WH EM |
|--------------------------------------|---|--------------|-----------|-----------|----------------------|
| Fixture                              | Series  | "EXIT" Color | Finish    | Input     |                      |
|                                      | <b>ES-L</b>                                     | <b>RG</b>    | <b>WH</b> | <b>EM</b> |                      |
| Options                              |   |              |           |           |                      |
| <b>A</b>                             | <b>SERIES</b>                                   |              |           |           |                      |
| ES-L Exit Sign with Emergency Lights |   |              |           |           |                      |
| <b>B</b>                             | <b>"EXIT" COLOR</b>                             |              |           |           |                      |
| Code                                 | Color   |              |           |           |                      |
| RG                                   | Red / Green Switchable                          |              |           |           |                      |
| <b>C</b>                             | <b>FINISH</b>                                   |              |           |           |                      |
| BK                                   | Black   |              |           |           |                      |
| WH                                   | White   |              |           |           |                      |
| <b>D</b>                             | <b>INPUT</b>                                    |              |           |           |                      |
| EM                                   | 120 Minute Battery                              |              |           |           |                      |
| <b>E</b>                             | <b>OPTIONS</b>                                  |              |           |           |                      |
| AIA                                  | Assembled in America, compliant with BAA (COTS) |              |           |           |                      |

## ES-L-RG-G2 SERIES EXIT SIGN with EMERGENCY LIGHTS

### DIMENSIONS

| Series  | L1             | L2             | H             | D            |
|---------|----------------|----------------|---------------|--------------|
| ES-L-RG | 18.06" (459mm) | 11.61" (295mm) | 7.17" (182mm) | 2.82" (72mm) |

