

## ELW SERIES WET LOCATION EMERGENCY LIGHT

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Injection-molded thermoplastic material. Spec-grade product obtain UL-94-5VA rated.  
Fully adjustable emergency lights offers 360° rotation and 90° tilt.

### OPTICS

Polycarbonate prismatic lens.

### ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature.  
Lamps use long-lasting, efficient ultra bright white LEDs.  
Adjustable 2 x 1.2W LED heads equipped with 12 series-parallel white LEDs each.  
120-277V Input, maintenance-free 3.6V 700mAh Nickel Cadmium battery that provides a minimum emergency duration of 120 minutes.

### MOUNTING

Surface mount through luminaire body, allow mounting on 4" Round or Square J-box.  
Suggested mounting height of 7.5ft illuminates 1 footcandle (FC) spaced at 28ft for a 3ft path of egress.

### EMERGENCY OPERATION

Upon failure of the normal utility power, an internal solidstate transfer switch automatically provides uninterrupted emergency operation for at least 120 minutes.  
Recharge a discharged battery in 24 hours.

### STANDARD FINISH

White finish with clear water tight cover.

### CERTIFICATION

All luminaires are built to UL1598 & UL924 standards and bear appropriate cULus labels.  
UL94-5VA Rating.

### WARRANTY

5 year warranty, see Limited Warranty for additional information



### SHIPPING DATA

| Product | Measurement      | Weight |
|---------|------------------|--------|
| ELW-A   | 12"L x 5"W x 5"H | 3 lb   |



## ELW SERIES WET LOCATION EMERGENCY LIGHT

| ORDER INFORMATION |                                                 |       |        | EXAMPLE : ELW A WH EM |  |  |
|-------------------|-------------------------------------------------|-------|--------|-----------------------|--|--|
| Fixture           | SERIES                                          | POWER | FINISH | INPUT                 |  |  |
|                   | ELW                                             | A     | WH     | EM                    |  |  |
| A                 | SERIES                                          |       |        |                       |  |  |
| ELW               | Wet Location Emergency Light                    |       |        |                       |  |  |
| B                 | POWER & LM                                      |       |        |                       |  |  |
|                   | Power                                           | LM    |        |                       |  |  |
| A                 | 2 x 1.2W                                        | 175lm |        |                       |  |  |
| C                 | FINISH                                          |       |        |                       |  |  |
| WH                | White                                           |       |        |                       |  |  |
| D                 | INPUT                                           |       |        |                       |  |  |
| EM                | 120 Minute Battery                              |       |        |                       |  |  |
| E                 | ACCESSORIES/OPTIONS                             |       |        |                       |  |  |
| BAA               | Assembled in America, compliant with BAA (COTS) |       |        |                       |  |  |

**ELW SERIES WET LOCATION EMERGENCY LIGHT**

**DIMENSIONS**

| Power | L              | W             | H             |
|-------|----------------|---------------|---------------|
| ELW-A | 11.61" (295mm) | 4.71" (112mm) | 4.13" (105mm) |

