

ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Sturdy thermoplastic, injection molded, 5VA flame retardant, high impact resistant housing.

OPTICS

Two "EXIT" Faceplates (with optional knockout arrows) and one blank faceplate included.

Color-matched diffuser eliminates hot spots and striations, providing optimal light output.

Exit sign meeting 100ft visibility compliant with UL requirement.

Emergency light capable of 0-90° horizontal x 180° vertical rotation.



LED Exit Sign with Emergency Lights RED Letters

ELECTRICAL

1.5W output per emergency light, total 3.1W consumption.

120-277V input.

3.6V 1000mAh Ni-Cad battery, 24hr for full charge at initial use or on depleted battery.

0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

MOUNTING

Suitable for ceiling mount, wall mount, mounting canopy included.

STANDARD FINISH

Black Finish

White Finish

CERTIFICATION

UL-94V-0 Flame Rating.

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.

All luminaires are built to UL924 standards and bear appropriate cETLus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information.

SHIPPING DATA

Product	Measurement	Weight
ES-L	17"L x 4"W x 8"H	4 lb



ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS

ORDER INFORMATION				EXAMPLE: ES-L R WH EM
Fixture	Series	"Exit" Color	Finish	Input
	ES-L	R	WH	EM
A	SERIES			
ES-L	LED Exit Sign with Dual Emergency Lights			
B	"EXIT" COLOR			
Code	Color			
G	Green			
R	Red			
C	FINISH			
BK	Black			
WH	White			
D	INPUT			
EM	90 Minute Battery			
E	ACCESSORIES/OPTIONS			
AIA	Assembled in America, compliant with BAA (COTS)			

ES-L SERIES LED EXIT SIGN with EMERGENCY LIGHTS

DIMENSIONS

Series	L1	L2	H	W1	W2
ES-L	17.00" (431.80mm)	11.73" (297.94mm)	7.36" (186.95mm)	4.32" (109.73mm)	1.97" (49.96mm)

