

## ES-RG SERIES LED EXIT SIGN

Client:  
Project:  
Type:  
Quantity:

### CONSTRUCTION

Engineering grade injection-molded thermoplastic. 5VA flame retardant, high-impact resistant.

### OPTICS

Double "EXIT" faceplates. (optional knockout arrows) included.  
Red / Green letters switchable.



### ELECTRICAL

Smart voltage input 120-277 VAC operation. LED display indicates AC/ON.  
An external push button test switch allows maintenance personnel to quickly determine the operational status of the unit.  
0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

Green "EXIT" Letters

### MOUNTING

Easy to install. Universal mounting canopy for top or side installation.  
Mounting canopy, installation instructions & hardware (inside unit).



### STANDARD FINISH

White / Black finish.

Red "EXIT" Letters

### CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.  
All luminaires are built to UL924 standards and bear appropriate cULus labels.

### SHIPPING DATA

Product	Measurement	Weight
ES-RG	13" L x 8" W x 2" H	3 lb

### WARRANTY

5 year warranty, see Limited Warranty for additional information



## ES-RG SERIES LED EXIT SIGN

ORDER INFORMATION					EXAMPLE: ES RG WH EM
Fixture	Series	"EXIT" Color	Finish	Input	
	<b>ES</b>	<b>RG</b>		<b>EM</b>	
<b>A</b>	<b>SERIES</b>				
ES	LED Exit Sign				
<b>B</b>	<b>"EXIT" COLOR</b>				
Code	Color				
RG	Red / Green Switchable				
<b>C</b>	<b>FINISH</b>				
BK	Black				
WH	White				
<b>D</b>	<b>INPUT</b>				
EM	120 Minute Battery				

**ES-RG SERIES LED EXIT SIGN****DIMENSIONS**

Series	L	H	D
ES-RG	12.20" (310mm)	7.44" (189mm)	1.69" (43mm)

