

SMPR G2 SERIES SURFACE MOUNT PANEL ROUND

Client:
 Project:
 Type:
 Quantity:

CONSTRUCTION

Offered in 5", 7", 9", 11", and 13" sizes, the fixture features a robust die-cast aluminum trim designed for surface mounting. Engineered for secure installation to standard junction boxes with enhanced durability and heat dissipation.

OPTICS

Edgelit panel, durable PMMA lens, gasketed and sealed prevent splash of water or dust object from entry.

ELECTRICAL

90+ CRI.
 120V Input Triac dimming.
 5 CCT selectable light engine 2700~5000K.
 Greater than 70% LED lumen maintenance at 50,000 hours.
 -20°C up to 45°C (-4°F up to 113°F) maximum operating temperature.

MOUNTING

New Construction: Surface Mount to standard depth 2.75" or 3.5" J-box.

STANDARD FINISH

Corrosion resistant White finish, suitable for wet locations.
 Decorative trim rings available in Brushed Nickel, Black, and Bronze.

CERTIFICATION

IP44 Wet location listed.
 Meets Buy America Act requirements.
 All luminaires are built to UL1598 standards and bear appropriate cETLus labels.
 Title 24 JA8 compliant; see local ordinance for qualification information.
 ENERGY STAR® certified for SMPR-G2-5, SMPR-G2-7, SMPR-G2-9 model.

WARRANTY

5 year warranty, see Limited Warranty for additional information.



Decorative Trim

SHIPPING DATA

| Product | Measurement | Weight |
|------------|-------------------|--------|
| SMPR-G2-5 | 6"L x 6"W x 1"H | 2 lb |
| SMPR-G2-7 | 8"L x 8"W x 1"H | 2 lb |
| SMPR-G2-9 | 9"L x 9"W x 1"H | 2 lb |
| SMPR-G2-11 | 11"L x 11"W x 1"H | 3 lb |
| SMPR-G2-13 | 13"L x 13"W x 1"H | 3 lb |



SMPR G2 SERIES SURFACE MOUNT PANEL ROUND

ORDER INFORMATION **EXAMPLE : SMPR G2 7 9SC WH S**

| Fixture | Series | Model | CCT | Finish | Input |
|---------|----------------|-------|-----------|-----------|----------|
| | SMPR-G2 | | SC | WH | S |

**Accessories
Options**

A SERIES

| | |
|----------------|---------------------------------|
| SMPR-G2 | Surface Mount Panel Round Gen 2 |
|----------------|---------------------------------|

B MODEL

| CODE | TRIM TYPE | POWER | LM |
|-----------|------------------|-------|---------------|
| 5 | 5-inch aperture | 10W | 829lm (avg.) |
| 7 | 7-inch aperture | 15W | 1174lm (avg.) |
| 9 | 9-inch aperture | 18W | 1394lm (avg.) |
| 11 | 11-inch aperture | 21W | 2029lm (avg.) |
| 13 | 13-inch aperture | 24W | 2183lm (avg.) |

C CCT

| | |
|------------|---|
| 9SC | 90 CRI Field Selectable 2700/3000/3500/4000/5000K |
|------------|---|

D FINISH

| | |
|-----------|--------------|
| WH | White finish |
|-----------|--------------|

E INPUT

| | |
|-----------|--------------------------|
| S | 120V Input Triac Dimming |
| SD | 120V Input 0-10V Dimming |

F ACCESSORIES/OPTIONS


| | |
|------------------------------|---|
| BAA | Assembled in America, compliant with BAA (COTS) |
| TRIM-SMPR-G2-5- ____ | SMPR-G2 5" Decorative Trim BN - Brushed Nickel BK - Black BZ - Bronze |
| TRIM-SMPR-G2-7- ____ | SMPR-G2 7" Decorative Trim BN - Brushed Nickel BK - Black BZ - Bronze |
| TRIM-SMPR-G2-9- ____ | SMPR-G2 9" Decorative Trim BN - Brushed Nickel BK - Black BZ - Bronze |
| TRIM-SMPR-G2-11- ____ | SMPR-G2 11" Decorative Trim BN - Brushed Nickel BK - Black BZ - Bronze |
| TRIM-SMPR-G2-13- ____ | SMPR-G2 13" Decorative Trim BN - Brushed Nickel BK - Black BZ - Bronze |
| CONTROL-XFAC* | AVI-ON Bluetooth Zone Controller Adapter |

*see page 5 for sensor spec

SMPR G2 SERIES SURFACE MOUNT PANEL ROUND

DIMENSIONS

| MODEL | W1 | W2 | H |
|------------|------------------|------------------|--------------|
| SMPR-G2-5 | ø 4.41" (113mm) | ø 5.51" (141mm) | 0.79" (21mm) |
| SMPR-G2-7 | ø 6.38" (163mm) | ø 7.48" (191mm) | 0.79" (21mm) |
| SMPR-G2-9 | ø 7.76" (198mm) | ø 8.86" (226mm) | 0.79" (21mm) |
| SMPR-G2-11 | ø 9.8" (250mm) | ø 10.98" (280mm) | 0.98" (26mm) |
| SMPR-G2-13 | ø 11.57" (295mm) | ø 12.8" (326mm) | 0.98" (26mm) |



APPLICATION

Surface Mount
 (Standard)



SMPR G2 SERIES SURFACE MOUNT PANEL ROUND

PERFORMANCE DATA

| SIZE (INCHES) | SYSTEM WATTS | VOLTAGE | 2700K (90CRI) | | 3000K (90CRI) | | 3500K (90CRI) | | 4000K (90CRI) | | 5000K (90CRI) | |
|---------------|--------------|---------|---------------|-----|---------------|-----|---------------|-----|---------------|-----|---------------|-----|
| | | | LUMENS | LPW |
| 5 | 10W | 120V | 771 | 78 | 812 | 82 | 858 | 86 | 860 | 87 | 846 | 85 |
| 7 | 15W | 120V | 1091 | 74 | 1149 | 78 | 1214 | 82 | 1217 | 82 | 1198 | 81 |
| 9 | 18W | 120V | 1296 | 75 | 1364 | 78 | 1442 | 82 | 1446 | 83 | 1423 | 82 |
| 11 | 21W | 120V | 1835 | 87 | 1939 | 93 | 2128 | 103 | 2161 | 103 | 2084 | 99 |
| 13 | 24W | 120V | 1973 | 85 | 2086 | 91 | 2289 | 101 | 2324 | 101 | 2242 | 97 |

SMPR G2 SERIES SURFACE MOUNT PANEL ROUND

SENSOR SPEC


| Model | Type | Mounting | Coverage | Input | Function | Programmable |
|---|-----------------------|----------|----------|------------|---|-----------------------------------|
| CONTROL-XFAC (see page 5 for detail) | Fixture Controller | - | - | 100-277VAC | Bluetooth On/Off/Dimming Scheduling | AVI-ON Bluetooth Mobile App |



CONTROL-XFAC

SMPR G2 SERIES SURFACE MOUNT PANEL ROUND

CONTROL-XFAC SPEC



SPECIFICATIONS

| | | | |
|------------------------|---|----------------------------------|---|
| INPUT VOLTAGE: | 100-277VAC | RADIO FREQUENCY: | 50/60Hz |
| CURRENT: | MIN: 20 / 14mA MAX: 81 / 46mA | RELAY CURRENT: | 16A |
| 0-10V DIMMING: | 100-277VAC | PROTECTION/IMMUNITY: | LEVEL 4 |
| SIZE: | 3.58" x 3.58" x 1.57" (91mm x 91mm x 40mm) | AMPERAGE FOR 0-10V LINES: | Contact Discharge: ± 8kV Air Discharge: ±12kV 325mA / CH |
| STORAGE TEMP: | -40°F to + 185°F (-40°C to + 85°C) | WARRANTY: | 5 years |
| OPERATING TEMP: | -4°F to + 113°F (-20°C to + 45°C) | REGULATORY: | FCC: 2AFZI-AVIBG21 IC: 20544-AVBG21 BQB: D059595, DID: 185220 UL 924, 2043 |

WIRING DIAGRAM

