



ES SERIES LED EXIT SIGN

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Sturdy thermoplastic, injection molded, V-0 flame retardant, high impact resistant housing.

OPTICS

Two "EXIT" Faceplates (with optional knockout arrows) and one blank faceplate included.

Color-matched diffuser eliminates hot spots and striations, providing optimal light output.

ELECTRICAL

0°C up to 40°C (32°F up to 104°F) maximum operating temperature. Designed for an expected life of 50,000 hours.

MOUNTING

Easy to install. Universal mounting canopy for top or side installation. Mounting canopy, installation instructions & hardware (inside unit).

STANDARD FINISH

Black Finish
White Finish

CERTIFICATION

All luminaires are built to UL1598 standards and bear appropriate cETLus labels.
All luminaires are built to UL924 standards and bear appropriate cULus labels.

WARRANTY

5 year warranty, see Limited Warranty for additional information



Green "EXIT" Letters



Red "EXIT" Letters

SHIPPING DATA

| Product | Measurement | Weight |
|---------|------------------|--------|
| ES | 12"L x 9"W x 3"H | 3 lb |



ES SERIES LED EXIT SIGN

| ORDER INFORMATION | | EXAMPLE: ES R WH EM | | |
|------------------------------|---|---------------------|-----------|-----------|
| Fixture | Series | "EXIT" Color | Finish | Input |
| | ES | | WH | EM |
| A SERIES | | | | |
| ES | LED Exit Sign | | | |
| B "EXIT" COLOR | | | | |
| Code | Color | | | |
| G | Green | | | |
| R | Red | | | |
| C FINISH | | | | |
| BK | Black | | | |
| WH | White | | | |
| D INPUT | | | | |
| EM | 120 Minute Battery | | | |
| E ACCESSORIES/OPTIONS | | | | |
| BAA | Assembled in America, compliant with BAA (COTS) | | | |

ES SERIES LED EXIT SIGN

DIMENSIONS

| Series | L | W | D |
|--------|----------------|---------------|--------------|
| ES | 12.01" (305mm) | 7.99" (203mm) | 2.09" (53mm) |

