

**HBH SERIES HIGH AMBIENT BAY LIGHT**

Client:  
 Project:  
 Type:  
 Quantity:

**CONSTRUCTION**

Single piece die-cast aluminum housing, driver enclosure thermally separated from body, maximizes heat dissipation & air flow.

Unique design allows luminaire to perform and sustain under high ambient temperature applications up to 65°C (149°F).

IP66 rated protection against dust and jets of water.

Suitable for interior/exterior, wet, high pressure hosedown applications.

**OPTICS**

Custom engineered high-efficient impact resistant and high temperature rating optics providing optimally controlled light distribution.

**ELECTRICAL**

70+ CRI LED.

-40°C up to 65°C\* (-40°F up to 149°F) maximum operating temperature.

Long-life 100,000 hr LED at L70 @ 25°C.

50/60Hz, <20% THD, 0.9 power factor.

Field Selectable Lumen Techonology.

Driver operates at 120-277V input, 0-10V dimmable driver, down to 10% with integral 12V AUX 3.5mm sensor receptacle for SENSOR-ANT-6-4T.

Optional 347/480V input.

Optional dimming sensor for occupancy and ambient light level detection.

**SENSORS (OPTIONAL)**

SENSOR-ANT-6-4T - Plug-N-Play PIR on/off/dimming/photosensing (40FT MH).

SENSOR-ANT-6-4T-H - Plug-N-Play PIR on/off/dimming/photosensing (50FT MH).

SENSOR-BLE-6-4T - Plug-N-Play PIR ALS Control Bluetooth/on/off/dimming (40FT MH).

SENSOR-BLE-6-4T-H - Plug-N-Play PIR ALS Control Bluetooth/on/off/dimming (50FT MH).

"-EM" - Compatible with Emergency Battery (Auto-bypass)

**MOUNTING**

Pendant mount 3/4" conduit entry on top of fixture with snap hook.

Optional 3/4" Pipe Adapter to Pendant Mount Application.

**STANDARD FINISH**

Corrosion resistant Dark Bronze powder coating finish.

**CUSTOM FINISH**

Corrosion resistant Black, Graphite Metallic, Gray, Silver, White or custom RAL#.

**CERTIFICATION**

IP66 Wet location label standard.

Meets Buy America Act requirements.

IK10 Impact Rated.

All luminaires are built to UL1598 standards and bear appropriate cULus labels.

DLC® Premium (DesignLights Consortium Qualified)

**WARRANTY**

5 year warranty, see Limited Warranty for additional information.



350W / 410W

**SHIPPING DATA**

Product	Measurement	Weight
HBH-350	26"L x 26"W x 8"H	18 lb
HBH-410	26"L x 26"W x 8"H	20 lb



**HBH SERIES HIGH AMBIENT BAY LIGHT**

**ORDER INFORMATION** **EXAMPLE : HBH 350 50 C DB UD**

<b>Fixture</b>	<b>Series</b>	<b>Power &amp; LM</b>	<b>CCT</b>	<b>Lens</b>	<b>Finish</b>	<b>Input</b>
	<b>HBH</b>		<b>50</b>	<b>C</b>	<b>DB</b>	

Accessories  
Options

**A SERIES**

**HBH** Bay Light - Field Selectable Lumen

**B POWER & LM**

CODE	POWER	LM	CODE	POWER	LM
<b>350</b>	MAX 350W (up to 55°C)	62,000	<b>410</b>	MAX 410W (up to 55°C)	72,000
	140W High Ambient (up to 65°C)	26,600		164W High Ambient (up to 65°C)	31,000
	210W High Ambient (up to 65°C)	39,000		246W High Ambient (up to 65°C)	45,500
	280W High Ambient (up to 65°C)	51,000		328W High Ambient (up to 55°C)	59,000
	350W High Ambient (up to 55°C)	62,000		410W High Ambient (up to 55°C)	72,000

**C CCT**

**50** 5000K

**D LENS**

**C** Clear

**F FINISH**

Standard

**DB** Dark Bronze

Custom Color

<b>CC</b>	<b>BK</b> Black	<b>GM</b> Graphite Metallic	<b>GR</b> Gray
	<b>SV</b> Silver	<b>WH</b> White	<b>RAL#</b>

**F INPUT**

**UD** 110-277V, 1-10V Dimmable, w/Integral 12V AUX 3.5mm sensor receptacle for SENSOR-ANT-6-4T

**HD** 347V, 480V, 1-10V Dimmable, w/Integral 12V AUX 3.5mm sensor receptacle for SENSOR-ANT-6-4T

## HBH SERIES HIGH AMBIENT BAY LIGHT

### G ACCESSORIES/OPTIONS

<b>BAA</b>	Assembled in America, compliant with BAA (COTS)
<b>MOUNT-HB-PIPE-BK</b>	3/4" Pipe Adapter to Pendant Mount Application
<b>REMOTE-RC100</b>	Handheld Remote Commissioning Tool for SENSOR-ANT (1 per job)
<b>SENSOR-ANT-6-4T*</b>	Plug-N-Play PIR on/off/dimming/photosensing up to <b>40FT MH</b>
<b>SENSOR-ANT-6-4T-EM*</b>	Plug-N-Play PIR on/off/dimming/photosensing for <b>EMB application</b> up to <b>40FT MH</b>
<b>SENSOR-ANT-6-4T-H*</b>	Plug-N-Play PIR on/off/dimming/photosensing up to <b>50FT MH</b>
<b>SENSOR-ANT-6-4T-H-EM*</b>	Plug-N-Play PIR on/off/dimming/photosensing for <b>EMB application</b> up to <b>50FT MH</b>
<b>SENSOR-BLE-6-4T*</b>	Plug-N-Play Bluetooth on/off/dimming/Daylight Harvesting Sensor (ALS Control Mobile App)
<b>SENSOR-BLE-6-4T-EM*</b>	Plug-N-Play Bluetooth on/off/dimming/Daylight Harvesting Sensor (ALS Control Mobile App) for EMB application
<b>SENSOR-BLE-6-4T-H*</b>	Plug-N-Play Bluetooth on/off/dimming/Daylight Harvesting Sensor (ALS Control Mobile App) up to <b>50FT MH</b>
<b>SENSOR-BLE-6-4T-H-EM*</b>	Plug-N-Play Bluetooth on/off/dimming/Daylight Harvesting Sensor (ALS Control Mobile App) for EMB application up to <b>50FT MH</b>
<b>-CORD</b>	18-3 300V 6 Foot Cord
<b>-PLUG</b>	18-3 300V 6 Foot and 3 Prong Plug
<b>TWIST-LOCK</b>	Specify Plug Type: <b>L515P / L715P / HBL5929 / L8-20P</b>


\*see page 6 for sensor spec

**HBH SERIES HIGH AMBIENT BAY LIGHT**


**DIMENSIONS**

Model	H1	H2	W1	W2
HBH-350 / 410	7.47" (190mm)		ø 24.25" (616mm)	
MOUNT-HB-PIPE-BK		3.15" (80mm)		ø 1.01" (26mm)

**Luminaire**



**Pipe Adapter**



**HBH SERIES HIGH AMBIENT BAY LIGHT**

**PERFORMANCE DATA**

SYSTEM WATTS	MAX AMBIENT TEMPERATURE	VOLTAGE	5000K	
			LUMENS	LPW
350W Set @ 140W	65°C	120-277 / 347/480V	26,600	190
350W Set @ 210W	65°C	120-277 / 347/480V	39,000	186
350W Set @ 280W	65°C	120-277 / 347/480V	51,000	182
350W Set @ 350W	55°C	120-277 / 347/480V	62,000	177
410W Set @ 164W	65°C	120-277 / 347/480V	31,000	189
410W Set @ 246W	65°C	120-277 / 347/480V	45,500	185
410W Set @ 328W	55°C	120-277 / 347/480V	59,000	180
410W Set @ 410W	55°C	120-277 / 347/480V	72,000	176

**DLC CODE**

Part Number	DLC Product ID	DLC Class
HBH-35050C-[DB, BK, WH] [UD,HD][Blank, SENSOR-BLE-619-L3/L4, SENSOR-ANT-6-4T]	S-J0FR6J	Premium
HBH-41050C-[DB, BK, WH] [UD,HD][Blank, SENSOR-BLE-619-L3/L4, SENSOR-ANT-6-4T]	S-2DZS5D	Premium

**HBH SERIES HIGH AMBIENT BAY LIGHT**

**SENSOR SPEC**

Model	Type	Mounting	Coverage	Input	Function	Programmable
SENSOR-ANT-6-4T SENSOR-ANT-6-4T-EM	PIR	up to 40FT	30FT radius	12V DC	On/Off/Dimming	REMOTE-RC100
SENSOR-BLE-6-4T SENSOR-BLE-6-4T-EM (see page 7 for detail)	PIR	up to 40FT	30FT radius	12V DC	Bluetooth Mesh On/Off/Dimming Daylight Harvesting	ALS Control Bluetooth Mobile App
SENSOR-ANT-6-4T-H* SENSOR-ANT-6-4T-H-EM	PIR	up to 50FT	30FT radius	12V DC	On/Off/Dimming	REMOTE-RC100
SENSOR-BLE-6-4T-H* SENSOR-BLE-6-4T-H-EM	PIR	up to 50FT	30FT radius	12V DC	Bluetooth Mesh On/Off/Dimming Daylight Harvesting	ALS Control Bluetooth Mobile App



- SENSOR-ANT-6-4T
- SENSOR-ANT-6-4T-EM
- SENSOR-BLE-6-4T
- SENSOR-BLE-6-4T-EM
- SENSOR-BLE-6-4T-H
- SENSOR-BLE-6-4T-EM-H

**FEATURE**


- **Installation:** Plug-N-Play via AUX socket on attached fixture
- **Commissioning:** Wirelessly through ALS Control Mobile App (iOS / Android)
- **Certification:** DLC 5.1 Networked Lighting Control System
- **Control:** Hold time, High-Low setting, continuous Bi-level dimming, Code-compliant manual-on or auto-off capability
- **Sensor:** Motion (Occupancy/Vacancy/Manual) and Daylight Harvesting
- **Room and Zone Control:** Zoning and Grouping control, Scheduling



**SPECIFICATIONS**



<b>SENSOR TYPE:</b>	Passive Infrared Sensor (PIR)
<b>WIRELESS STANDARDS:</b>	5.0 Bluetooth Mesh
<b>STANDARD OPTION:</b>	SENSOR-BLE-6-4T
<b>EMB OPTION:</b>	SENSOR-BLE-6-4T-EM (Designed for fixtures with emergency kit. When the voltage power is off, the sensor will stop working.)
<b>INPUT VOLTAGE:</b>	12-24VDC, >50mA
<b>CONTROL OUTPUT:</b>	0-10V
<b>OPERATING TEMP:</b>	-4°F ~ +140°F (-20°C ~ +60°C)
<b>COMMISSIONING RANGE:</b>	50FT
<b>BLUETOOTH RANGE:</b>	164FT
<b>DETECTION ANGLE:</b>	360°
<b>MOUNTING HEIGHT:</b>	Up to 40FT
<b>WARRANTY:</b>	5 years
<b>IP RATING:</b>	IP65
<b>FACTORY DEFAULT SETTINGS:</b>	100% Brightness for 5 min Dim Down to 30% Hold for 10 min Turn Off

**DIMENSIONS**



H	W
1.03" (26.2mm)	2.17" (55mm)

**COVERAGE PATTERNS**



**ORDER CODES**

- SENSOR-BLE-6-4T** "Plug-N-Play" Integral Bluetooth Daylight Harvesting Sensor (ALS Control Mobile App) up to 40FT MH.
- SENSOR-BLE-6-4T-EM** "Plug-N-Play" Integral Bluetooth Daylight Harvesting Sensor (ALS Control Mobile App) up to 40FT MH w/ EMB.
- SENSOR-BLE-6-4T-H** "Plug-N-Play" Integral Bluetooth Daylight Harvesting Sensor (ALS Control Mobile App) up to 50FT MH.
- SENSOR-BLE-6-4T-H-EM** "Plug-N-Play" Integral Bluetooth Daylight Harvesting Sensor (ALS Control Mobile App) up to 50FT MH w/ EMB.

