

CPGM SERIES FUEL STATION CANOPY

Client:
Project:
Type:
Quantity:

CONSTRUCTION

Rugged die-cast aluminum housing with corrosion resistant powder coat finish.
Heat dissipating fins provide superior thermal performance extending the life of the luminaire.
LED array and electrical components are in insulated compartment.
Suitable for surface or pendant installation.

OPTICS

Tempered glass lens designed for maximum protection and excellent efficiency.
Standard Type V Distribution, available option for Type III.

ELECTRICAL

80+ CRI Lumileds LED.
-40°C up to 45°C (-40°F up to 113°F) maximum operating temperature
160,000 hr at L70 @ 25°C, 75,000 hr at L70 40°C.
Driver operates at 120-277V input, 50/60Hz. <20% THD, 0.9 power factor.
Optional 347V / 480V Driver.

SENSORS (OPTIONAL)

SENSOR-BLE-7D Integral Microwave sensor ALS Control bluetooth/on/off/dimming/
photosensing.
CONTROL-LVFA AVI-ON Bluetooth Mesh Controller.

MOUNTING

3/4" conduit entry on top for pendant mount.
Surface mount box included.

STANDARD FINISH

Corrosion resistant White powder coating finish.

CUSTOM FINISH

Corrosion resistant Dark Bronze, Black, Graphite Metallic, Gray, Silver, or custom RAL#.

CERTIFICATION

Meets Buy America Act requirements.
IP66 Wet location label standard.
All luminaires are built to UL1598 standards and bear appropriate cULus labels.
For Emergency application, equipment with UL924 certified battery packs.
DLC® Premium (DesignLights Consortium Qualified)

WARRANTY

5 year warranty, see Limited Warranty for additional information.



SHIPPING DATA

Product	Measurement	Weight
CPGM-100	16"L x 16"W x 5"H	11 lb
CPGM-135	16"L x 16"W x 5"H	11 lb
CPGM-150	16"L x 16"W x 5"H	14 lb



CPGM SERIES FUEL STATION CANOPY

ORDER INFORMATION					EXAMPLE : CPGM 100 50 T5 SM WH UD			
	Fixture	Series	Power & LM	CCT	Distribution	Mounting	Finish	Input
		CPGM	100	50	T5	SM	WH	UD
Accessories Options								
A	SERIES							
	CPGM	Fuel Station Canopy						
B	POWER & LM							
	Code	Power	LM					
	100	100W	15,000					
	135	135W	21,000					
	150	150W	23,500					
C	CCT							
	40	4000K						
	50	5000K						
D	DISTRIBUTION							
	T3	Type III distribution (made to order)						
	T5	Type V distribution (standard)						
E	MOUNTING							
	SM	4" Stem with Surface Mount Box (3/4" conduit entry on top center)						
F	FINISH							
	Standard							
	WH	White						
	Custom Color							
	CC	DB	Dark Bronze	BK	Black	GM	Graphite Metallic	
		GR	Gray	SV	Silver	RAL#		
G	INPUT							
	UD	120-277V, 1-10V Dimming						
	HD	347-480V, 1-10V Dimming						
H	ACCESSORIES/OPTIONS							
	AIA	Assembled in America, compliant with BAA (COTS)						
	SENSOR-BLE-7D*	Integral Bluetooth Microwave Motion Sensor (ALS Control Mobile App)						
	CONTROL-LVFA*	AVI-ON Bluetooth Mesh Control System						

*see page 4 for sensor spec

CPGM SERIES FUEL STATION CANOPY

Dimensions

Power	L1	L2	W1	W2	H1	H2
100W / 135W / 150W	15.75" (400mm)	8.58" (218mm)	15.75" (400mm)	14.65" (372mm)	8.78" (223mm)	7.28" (185mm) Including a 4" long 3/4" Stem

